

Frame size	Rated output power	Rated current at			Full-load speed rpm	Full-load power factor	Full-load efficiency	Full-load torque	Starting current	Starting torque	Pull-out torque	Sound pressure level	Weight foot mounted
		P <sub>N</sub> kW	230 V I <sub>u</sub> A	400 V I <sub>u</sub> A									
AMA-HB 90 S	0.75	3.43	1.98		934	0.72	75.9	7.67	4.5	2.2	2.4	51	18.5
AMA-HB 90 L	1.10	4.88	2.82		945	0.72	78.1	11.1	4.5	2.4	2.6	51	21
AMA-HB 100 L	1.50	6.25	3.61		945	0.75	79.8	15.2	4.5	1.8	2.2	53	28.5
AMA-HB 112 M	2.20	8.83	5.10		960	0.76	81.8	21.9	4.5	2.3	2.8	58	33.5
AMA-HB 132 S	3.00	11.83	6.83		964	0.76	83.3	29.7	4.5	1.8	2.4	58	44
AMA-HB 132 M	4.00	15.5	8.96	5.17	965	0.76	84.6	39.6	5	2.9	2.7	59	53
AMA-HB 132 Mx	5.50		12	6.93	965	0.77	86.0	54.4	5.5	1.9	2.8	61	63.5
AMA-HB 160 M	7.50		15.9	9.18	970	0.78	87.2	73.8	6.5	2	3	61	100
AMA-HB 160 L	11.0		22.9	13.22	970	0.78	88.7	108.3	7.5	2.4	3.3	62	113

EN60034-1(IEC-DIN)

230/400V -50Hz, 400/690v -50Hz

Detachable feet from size 56-160

Colour Ral 5010

Information provided by  
**EMAG**  
 Tel: 01902 601403  
[www.emag-ltd.co.uk](http://www.emag-ltd.co.uk)