




Specification	IEC 60034-1
Manufacturer	AmTecs
Motor type	AMA 71 K4
Rated power	0.25 kW S1 Duty
Speed	1390 rpm
Voltage	220V / 400V
Frequency	50 Hz
Connection	Delta / Star
Full load current	1.3 A / 0.75 A
No-load current	
Enclosure	IP55
Insulation class	F (temp. rise B)
Max. ambient temp	40 °C
Max. altitude	1000 mtr above sea level
Comment	
Cable entry	M20 x 1.5
Construction	Aluminium
Weight	6.5 Kg
Type number	
Warranty	

Efficiency class	IE1
Load data	100%
Efficiency	65 %
Power factor	0.74
Sound pressure level (1m)	45 dB(A)
Resistance R20 (open)	
Resistance R20 (Delta)	

Full load torque	1.72 Nm
Starting / Full load torque	2.1
Pull up / Full load torque	
Pull out / Full load torque	2.2

Starting / Full load current (DOL)	5.2
Starting / Full load current (Y/D)	
Rotor Inertia	
Bearing DE	6202
Bearing NDE	6202

Electric Motors And Gearboxes Ltd
103 Morgan Close
Willenhall
West Midlands
WV12 4LH
01902 601403
sales@emag-ltd.co.uk



www.emag-ltd.co.uk