




Specification **IEC 60034-1**
 Manufacturer **AmTecs**
 Motor type **AMA 71 G4**
 Rated power **0.37 kW S1 Duty**
 Speed **1375 rpm**
 Voltage **220V / 400V**
 Frequency **50 Hz**
 Connection **Delta / Star**
 Full load current **1.85 A / 1.06 A**
 No-load current
 Enclosure **IP55**
 Insulation class **F (temp. rise B)**
 Max. ambient temp **40 °C**
 Max. altitude **1000 mtr above sea level**
 Comment
 Cable entry **M20 x 1.5**
 Construction **Aluminium**
 Weight **7 Kg**
 Type number
 Warranty

Efficiency class **IE1**
 Load data **100%**
 Efficiency **67 %**
 Power factor **0.75**
 Sound pressure level (1m) **45 dB(A)**
 Resistance R20 (open)
 Resistance R20 (Delta)

Full load torque **2.57 Nm**
 Starting / Full load torque **2.1**
 Pull up / Full load torque
 Pull out / Full load torque **2.2**

Starting / Full load current (DOL) **5.2**
 Starting / Full load current (Y/D)
 Rotor Inertia
 Bearing DE **6202**
 Bearing NDE **6202**

Electric Motors And Gearboxes Ltd
 103 Morgan Close
 Willenhall
 West Midlands
 WV12 4LH
 01902 601403
 sales@emag-ltd.co.uk



www.emag-ltd.co.uk