


Specification **IEC 60034-1**
 Manufacturer **AmTecs**
 Motor type **AMA-HO 71G4**
 Rated power **0.55 kW S1 Duty**
 Speed **1650 rpm**
 Voltage **110V / 190V**
 Frequency **50 Hz**
 Connection **Delta / Star**
 Full load current **6.17A / 3.56 A**
 No-load current
 Enclosure **IP55**
 Insulation class **F (temp. rise B)**
 Max. ambient temp **40 °C**
 Max. altitude **1000 mtr above sea level**
 Comment
 Cable entry
 Construction **Aluminium**
 Weight **7.5 Kg**
 Type number
 Warranty

Efficiency class **N/A**
 Load data **100%**
 Efficiency
 Power factor **0.72**
 Sound pressure level (1m) **49 dB(A)**
 Resistance R20 (open)
 Resistance R20 (Delta)
 Full load torque **3.8 Nm**
 Starting / Full load torque **2.2**
 Pull up / Full load torque
 Pull out / Full load torque **2.4**
 Starting / Full load current (DOL) **6**
 Starting / Full load current (Y/D)
 Rotor Inertia
 Bearing DE
 Bearing NDE

| | |
|---|--|
| <p>EMAG ELECTRIC MOTORS AND GEARBOXES LTD</p> |  www.emag-ltd.co.uk |
| <p>www.emag-ltd.co.uk</p> | |