



Specification IEC 60034-1
Manufacturer AmTecs
Motor type AMA 90 L8
Rated power 0.55 kW S1 Duty
Speed 700 rpm
Voltage 220V / 400V
Frequency 50 Hz
Connection Delta / Star
Full load current 3.59 A / 2.07 A
No-load current
Enclosure IP55
Insulation class F (temp. rise B)
Max. ambient temp 40 °C
Max. altitude 1000 mtr above sea level
Comment
Cable entry M20 x 1.5
Construction Aluminium
Weight 17.6 Kg
Type number
Warranty

Efficiency class IE1
Load data 100%
Efficiency 63 %
Power factor 0.61
Sound pressure level (1m) 49 dB(A)
Resistance R20 (open)
Resistance R20 (Delta)
Full load torque 7.5 Nm
Starting / Full load torque 1.8
Pull up / Full load torque
Pull out / Full load torque 2

Starting / Full load current (DOL) 4
Starting / Full load current (Y/D)
Rotor Inertia
Bearing DE 6205
Bearing NDE 6205

Electric Motors And Gearboxes Ltd
 103 Morgan Close
 Willenhall
 West Midlands
 WV12 4LH
 01902 601403
 sales@emag-ltd.co.uk



www.emag-ltd.co.uk