



Specification IEC 60034-1
Manufacturer AmTecs
Motor type AMA-IE2 90 L4
Rated power 1.5 kW S1 Duty
Speed 1445 rpm
Voltage 220V / 400V
Frequency 50 Hz
Connection Delta / Star
Full load current 5.87 A / 3.39 A
No-load current
Enclosure IP55
Insulation class F (temp. rise B)
Max. ambient temp 40 °C
Max. altitude 1000 mtr above sea level
Comment
Cable entry M20 x 1.5
Construction Aluminium
Weight 21 Kg
Type number
Warranty

Efficiency class IE2
Load data 100%
Efficiency 82.8 %
Power factor 0.77
Sound pressure level (1m) 54 dB(A)
Resistance R20 (open)
Resistance R20 (Delta)

Full load torque 9.91 Nm
Starting / Full load torque 3.2
Pull up / Full load torque
Pull out / Full load torque 3.8

Starting / Full load current (DOL) 6.8
Starting / Full load current (Y/D)
Rotor Inertia
Bearing DE 6205
Bearing NDE 6205

Electric Motors And Gearboxes Ltd
 103 Morgan Close
 Willenhall
 West Midlands
 WV12 4LH
 01902 601403
 sales@emag-ltd.co.uk



www.emag-ltd.co.uk