



Quantity	Title/Name, designation, material, dimension etc			Article No./Reference	
Designed by	Checked by	Approved by - date	File name	Date	Scale
			AMA 160M (B5)	29/04/2015	1:3
<b>AMTECS LTD</b>			AMA 160M (B5)		
				Edition	Sheet
				0	1/1

**Specification IEC 60034-1**  
**Manufacturer AmTecs**  
**Motor type AMA-IE2 160 M2**  
**Rated power 11 kW S1 Duty**  
**Speed 2930 rpm**  
**Voltage 400V / 690V**  
**Frequency 50 Hz**  
**Connection Delta / Star**  
**Full load current 19.9 A / 11.49 A**  
**No-load current**  
**Enclosure IP55**  
**Insulation class F (temp. rise B)**  
**Max. ambient temp 40 °C**  
**Max. altitude 1000 mtr above sea level**  
**Comment**  
**Cable entry M32 x 1.5**  
**Construction Aluminium**  
**Weight 96 Kg**  
**Type number**  
**Warranty**

**Efficiency class IE2**  
**Load data 100%**  
**Efficiency 89.4 %**  
**Power factor 0.89**  
**Sound pressure level (1m) 71 dB(A)**  
**Resistance R20 (open)**  
**Resistance R20 (Delta)**  
**Full load torque 35.85Nm**  
**Starting / Full load torque 2.2**  
**Pull up / Full load torque**  
**Pull out / Full load torque 2.9**  
**Starting / Full load current (DOL) 7.6**  
**Starting / Full load current (Y/D)**  
**Rotor Inertia**  
**Bearing DE 6209**  
**Bearing NDE 6209**

Electric Motors And Gearboxes Ltd  
 103 Morgan Close  
 Willenhall  
 West Midlands  
 WV12 4LH  
 01902 601403  
 sales@emag-ltd.co.uk



www.emag-ltd.co.uk