



Specification **IEC 60034-1**
 Manufacturer **AmTecs**
 Motor type **AMA-IE2 132 S2**
 Rated power **5.5 kW S1 Duty**
 Speed **2937 rpm**
 Voltage **400V / 690V**
 Frequency **50 Hz**
 Connection **Delta / Star**
 Full load current **10.6 A / 6.12 A**
 No-load current
 Enclosure **IP55**
 Insulation class **F (temp. rise B)**
 Max. ambient temp **40 °C**
 Max. altitude **1000 mtr above sea level**
 Comment
 Cable entry **M25 x 1.5**
 Construction **Aluminium**
 Weight **47.5 Kg**
 Type number
 Warranty

Efficiency class **IE2**
 Load data **100%**
 Efficiency **87 %**
 Power factor **0.86**
 Sound pressure level (1m) **70 dB(A)**
 Resistance R20 (open)
 Resistance R20 (Delta)
 Full load torque **17.88Nm**
 Starting / Full load torque **2.7**
 Pull up / Full load torque
 Pull out / Full load torque **3.5**
 Starting / Full load current (DOL) **7.5**
 Starting / Full load current (Y/D)
 Rotor Inertia
 Bearing DE **6308**
 Bearing NDE **6208**

Electric Motors And Gearboxes Ltd
 103 Morgan Close
 Willenhall
 West Midlands
 WV12 4LH
 01902 601403
 sales@emag-ltd.co.uk



www.emag-ltd.co.uk