

Frame size	Rated output power	Rated current at			Full-load speed rpm	Full-load power factor	Full-load efficiency	Full-load torque	Starting current	Starting torque	Pull-out torque	Sound pressure level	Weight foot mounted
		230 V I _L A	400 V I _L A	690 V I _L A									
AMA 63 K6	0.09	0.89	0.51		830	0.67	38	1.04	4	1.7	2	42	5.3
AMA 63 G6	0.12	1.02	0.58		830	0.68	40	1.38	4	1.7	2	42	6
AMA 71 K6	0.18	1.22	0.70		880	0.63	59	1.95	4	1.9	2	42	6.3
AMA 71 G6	0.25	1.56	0.90		900	0.68	59	2.65	4	1.9	2	42	6.7
AMA 80 K6	0.37	2.14	1.23		915	0.7	62	3.86	4.7	1.9	2	49	8.8
AMA 80 G6	0.55	2.95	1.70		920	0.72	65	5.71	4.7	1.9	2.1	49	10
AMA 90 S6	0.75	3.79	2.18		930	0.72	69	7.7	5.5	2	2.1	51	12.6
AMA 90 L6	1.10	5.25	3.02		930	0.73	72	11.3	5.5	2	2.1	51	16.6
AMA 100 L6	1.50	6.61	3.80		945	0.75	76	15.16	5.5	2	2.1	53	25
AMA 112 M6	2.20	9.20	5.29		945	0.76	79	22.23	6.5	2	2.1	58	35
AMA 132 S6	3.00	12.23	7.03		960	0.76	81	29.84	6.5	2.1	2.1	58	48
AMA 132 M6	4.00	16.11	9.26	5.37	960	0.76	82	39.79	6.5	2.1	2.1	59	51
AMA 132 Mx6	5.50		12.27	7.12	960	0.77	84	54.71	6.5	2.1	2.1	61	56
AMA 160 M6	7.50		15.7	9.0	970	0.8	86	74	6.5	2	2	61	74
AMA 160 L6	11.0		22.9	13.2	970	0.79	87.5	108	6.5	2	2	62	89

EN60034-1(IEC-DIN)

230/400V -50Hz, 400/690v -50Hz

Detachable feet from size 56-160

Color Ral 5010

Information provided by **EMAG**
 Tel: 01902 601403
 www.emag-ltd.co.uk