



Frame Size	A	B	C	D	E	F	G	H	K	M	N	P	S	T	M	N	P	S	T	M	N	P	S	T	AB	BB	AC	AD	HD	L
										IM B14					IM B14L					IM B5										
56	90	71	36	9	20	3	7.2	56	5.8	65	50	80	M5	2.5	85	70	105	M6	2.5	100	80	120	7	3	108	89	110	100	156	
63	100	80	40	11	23	4	8.5	63	7	75	60	90	M5	2.5	100	80	120	M6	3	115	95	140	10	3	125	103	120	109	172	250
71	112	90	45	14	30	5	11	71	7	85	70	105	M6	2.5	115	95	140	M8	3	130	110	160	10	3.5	140	113	140	110	181	290
80	125	100	50	19	40	6	15.5	80	10	100	80	120	M6	3	130	110	160	M8	3.5	165	130	200	12	3.5	155	122	158	135	215	337
90S	140	100	56	24	50	8	20	90	10	115	95	140	M8	3	130	110	160	M8	3.5	165	130	200	12	3.5	175	155	175	145	235	385
90L	140	125	56	24	50	8	20	90	10	115	95	140	M8	3	130	110	160	M8	3.5	165	130	200	12	3.5	175	155	175	145	235	385
100L	160	140	63	28	60	8	24	100	12	130	110	160	M8	3.5	165	130	200	M10	3.5	215	180	250	14.5	4	205	176	196	155	255	445
112M	190	140	70	28	60	8	24	112	12	130	110	160	M8	3.5	165	130	200	M10	3.5	215	180	250	14.5	4	235	180	220	170	282	455
132S	216	140	89	38	80	10	33	132	12	165	130	200	M10	3.5	215	180	250	M12	4	265	230	300	14.5	4	266	180	260	190	322	540
132M	216	178	89	38	80	10	33	132	12	165	130	200	M10	3.5	215	180	250	M12	4	265	230	300	14.5	4	266	218	260	190	322	580

Aluminium and cast iron three-phase squirrel cage induction brake motors with hand release according to IEC/DIN. Aluminium and Aluminium high output have multi-mount design, with removable feet. Voltage 220-240/380-420V or 380-420/660-720V, 50Hz, Insulation class F, Class B Temperature rise, Protection IP55, Colour RAL5010, NSK Bearings, DC Brake with halfwave rectifier.

Flange motors B5, B14 small available up to and including size 160. B14 large to 132.