

# ODE-3-140041-3F12

Optidrive E3 VFD Datasheet

**1.5 kW (2 HP), 4.1 A, 380-480 V, 3PH**  
IP20 Variable Frequency Drive with EMC Filter



### Input Ratings

Supply Voltage	380-480 V
Input Phases	3
Supply Current Continuous	5.6 A
Supply Fuse or MCB (Type B)	10 A

### Output Ratings

Motor Output Rating	1.5 kW (2 HP)
Output Voltage	0 – Supply Voltage
Output Current	4.1 A

### Cable Information

Max Supply Cable Size	8 mm <sup>2</sup> (0.01 sq in)
Max Motor Cable Size	8 mm <sup>2</sup> (0.01 sq in)
Max Motor Cable Length	100 m (328 ft)

### Factory Build Options

EMC Filter	Internal EMC Filter
Brake Transistor	No Internal Brake Transistor
Enclosure	IP20
Display	
PCB Coating	


### Dimensions

Size	1
Height	173 mm (6.81 in)
Width	83 mm (3.27 in)
Depth	123 mm (4.84 in)
Weight	1 kg (2.2 lbs)
Fixings	4 x M5

### Packaged Dimensions

Height	165 mm (6.5 in)
Width	125 mm (4.92 in)
Depth	235 mm (9.25 in)
Weight	1.2 kg (2.65 lbs)



 **Buy this drive or get more information**  
Find your local sales partner on [inverterdrives.com](http://inverterdrives.com)

Electric Motors And Gearboxes Ltd  
103 Morgan Close  
Willenhall  
West Midlands  
WV12 4LH  
01902 601403  
[sales@emag-ltd.co.uk](mailto:sales@emag-ltd.co.uk)



[www.emag-ltd.co.uk](http://www.emag-ltd.co.uk)