

# ODE-3-240058-3F4B

Optidrive E3 VFD Datasheet

**2.2 kW (3 HP), 5.8 A, 380-480 V, 3PH**

IP66 Outdoor Switched Variable Frequency Drive with EMC Filter



### Input Ratings

Supply Voltage	380-480 V
Input Phases	3
Supply Current Continuous	7.5 A
Supply Fuse or MCB (Type B)	16 A

### Output Ratings

Motor Output Rating	2.2 kW (3 HP)
Output Voltage	0 – Supply Voltage
Output Current	5.8 A

### Cable Information

Max Supply Cable Size	8 mm <sup>2</sup> (0.01 sq in)
Max Motor Cable Size	8 mm <sup>2</sup> (0.01 sq in)
Max Motor Cable Length	100 m (328 ft)

### Factory Build Options

EMC Filter	Internal EMC Filter
Brake Transistor	Internal Brake Transistor
Enclosure	IP66 Outdoor Switched
Display	
PCB Coating	

### Dimensions

Size	2
Height	257 mm (10.12 in)
Width	188 mm (7.4 in)
Depth	186 mm (7.32 in)
Weight	3.5 kg (7.72 lbs)
Fixings	4 x M4

### Packaged Dimensions

Height	215 mm (8.46 in)
Width	235 mm (9.25 in)
Depth	375 mm (14.76 in)
Weight	4.2 kg (9.26 lbs)



**Buy this drive or get more information**  
Find your local sales partner on [inverterdrives.com](http://inverterdrives.com)

Electric Motors And Gearboxes Ltd  
103 Morgan Close  
Willenhall  
West Midlands  
WV12 4LH  
01902 601403  
[sales@emag-ltd.co.uk](mailto:sales@emag-ltd.co.uk)



[www.emag-ltd.co.uk](http://www.emag-ltd.co.uk)